

CS 683 Emerging Technologies
Fall Semester, 2004
Doc 13 Cocoon Form
Contents

Contents	1
References	2
Cocoon Forms	3
Simple Example	3
formExample/sitemap.xmap	4
formExample/resources/form.html	5
formExample/content/age.xsp	6
formExample/style/main.xsl	7

Copyright ©, All rights reserved. 2004 SDSU & Roger Whitney,
5500 Campanile Drive, San Diego, CA 92182-7700 USA.
OpenContent (<http://www.opencontent.org/opl.shtml>) license
defines the copyright on this document.

References

Cocoon Developer's Handbook, Moczar & Aston, Sams Publishing, 2003

Cocoon Forms

Simple Example

Files

In CATALINA_HOME/webapps/cocoon/

formExample/content/age.xsp

formExample/resources/form.html

formExample/style/main.xsl

formExample/sitemap.xmap

<http://bismarck.sdsu.edu:9006/cocoon/age/index.html>

formExample/sitemap.xmap

```
<?xml version="1.0"?>
<map:sitemap xmlns:map="http://apache.org/cocoon/sitemap/1.0">
  <map:components>
    <map:generators default="file" />
    <map:transformers default="xslt" />
    <map:readers default="resources" />
    <map:serializers default="html" />
    <map:selectors default="browser" />
    <map:matchers default="wildcard" />
  </map:components>
  <map:pipelines>
    <map:pipeline>
      <map:match pattern="index.html">
        <map:read type="resource"
          src="resources/form.html" mime-type="text/html">
        </map:read>
      </map:match>
      <map:match pattern="processAge.html">
        <map:generate type="serverpages" src="content/age.xsp" />
        <map:transform type="xslt" src="style/main.xsl" />
        <map:serialize type="html" />
      </map:match>
    </map:pipeline>
  </map:pipelines>
</map:sitemap>
```

formExample/resources/form.html

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.1//EN"
  "http://www.w3.org/TR/xhtml11/DTD/xhtml11.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en">
  <head>
    <meta http-equiv="content-type" content="text/html;
      charset=iso-8859-1" />
    <title>
      Form Example
    </title>
  </head>
  <body>
    <h1>
      Form Example
    </h1>
    <form action="processAge.html" method="get">
      <label for="age">
        Enter your age:
      </label>
      <input type="text" id="age" name="age" value="10"
        size="40" />
      <input type="submit" />
    </form>
  </body>
</html>
```

formExample/content/age.xsp

```
<?xml version="1.0"?>
```

```
<xsp:page language="java"  
  xmlns:xsp="http://apache.org/xsp"  
  xmlns:xsp-request="http://apache.org/xsp/request/2.0" >
```

```
<page>  
  <xsp:logic>  
    String ageString = <xsp-request:get-parameter name="age" />;  
  </xsp:logic>  
  <title>Age Results</title>  
  <content>  
    <paragraph>You entered: <xsp:expr>ageString</xsp:expr>  
  </paragraph>  
  </content>  
</page>  
</xsp:page>
```

formExample/style/main.xsl

```
<?xml version="1.0"?>
<xsl:stylesheet version="1.0"
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform">

  <xsl:template match="page">
    <html>
      <head>
        <title>
          <xsl:value-of select="title"/>
        </title>
      </head>
      <body>
        <xsl:apply-templates/>
      </body>
    </html>
  </xsl:template>

  <xsl:template match="title">
    <h2>
      <xsl:apply-templates/>
    </h2>
  </xsl:template>

  <xsl:template match="paragraph">
    <p>
      <xsl:apply-templates/>
    </p>
  </xsl:template>
</xsl:stylesheet>
```